

1332/1432 Hinge Options

Application	Hinge Cup	Optional Accuride Hardware Kit	Mfg. P/N	Door Thickness		Max. Tab		Min. Door Gap				
				mm	inches	mm	inches	mm	inches	mm	inches	
Inset	35mm	4180-0389-XE Zinc Finish 4180-0407-XE Black Finish	Salice Supplied with 1332, Self Close C2P7A33 Zinc Free Swing C2P5A99 Base BAR3P39	19	3/4	8	5/16	2.3	3/32 ■ ▲	1.4	1/16	
				20.6	13/16	9 ■	11/32 ■	1.8	1/16 ●	.3	1/64	
		● Requires hinge lateral adjustment to achieve door gap. ■ May require notching. ▲ For smaller door gap, increase tab.										
		N/A	Blum Self Close 71M9550 Free Swing 70M9550 Base 175H9100	19	3/4	8	5/16	3.3 ■	1/8 ■ ▲	5.4	7/32	
				20.6	13/16					3.8	5/32	
				22.2	7/8					2.2	3/32	
			Grass G366Overlay Base B3H/RZ-0	19	3/4	8*	5/16*	2.3+	3/32+	6.0	1/4	
				20.6	13/16					4.4	3/16	
				22.2	7/8					2.8	1/8	
		* Requires 3mm (1/8") notch to the back of door. + With hinge adjusted all the way in. ▲ For smaller door gap, increase tab.										
		Mepla Self Close DS05-253S/00 Free Swing DS05-153S/00 Base DS 7250 ES 37 00	19	3/4	6.5	1/4	1.8 ●	1/16 ●	2.4	3/32		
			20.6	13/16					.8	1/32		
Inset for Thick Doors	40mm	4180-0394-XE	Salice Zinc Self Close CFA7G99 Zinc Free Swing CFA5G99 Base 3mm BAR3P39	19	3/4	15	19/32	2.3	3/32	14.4	9/16	
				20.6	13/16					12.8	1/2	
				22.2	7/8					11.2	7/16	
				23.8	15/16					9.6	3/8	
				25.4	1					8.0	5/16	
				27	1-1/16					6.4	1/4	
				28.6	1-1/8					4.8	3/16	
				30.2	1-3/16					3.2	1/8	
				31.8	1-1/4					1.6	1/16	
		N/A	Mepla Self Close DS25-253 S/00 Base DS 7250 ES 37 00	19	3/4	8	5/16	1.3	1/16	7.0	9/32	
				20.6	13/16					5.4	7/32	
				22.2	7/8					3.8	5/32	
				23.8	15/16					2.2	3/32	
				25.4	1					.6	1/32	
			27+	1-1/16+	2.0	3/32						
			28.6+	1-1/8+	.4	1/32						
			30.2*◆	1-3/16*◆	1.8	1/16						
			31.8*◆	1-1/4*◆	0	0						
* Requires 3mm (1/8") notch to the back of door. + Requires 1 spacer, 3mm (1/8"). ◆ Requires 2 spacers, 6mm (1/4")												
Overlay Amount												
Overlay		4180-0292-XE	Salice Zinc Self Close CFA7A99 Zinc Free Swing CFA5A99 Base BAR3P09	19	3/4	15	19/32	11.7	7/16	.4	1/64	

For Additional Hinges - Add 1 more spacer to secondary hinges.

Note: On thicker doors, mortise hinge cup into door back to improve door-to-slide clearance.

CAUTION: For doors under 36" tall, hinge carrier strip needs to be modified.

Hinge carrier strip required for all doors.

Accuride
www.accuride.com