

Application Guide for Flipper Door & Pocket Door Slides

	HORIZONTAL FLIPPER DOORS			VERTICAL POCKET DOORS			MAXIMUM DOOR DIMENSIONS		
	UNDER TOP BRACKET	UNDER TOP CEILING	OVER THE TOP	SIDE	PARTITION	BRACKET	WEIGHT	HEIGHT**	THICKNESS
117		●		●	●		25 lbs.	36"	3/4" ♦ MIN.
1145			●				30 lbs.	36"	3/4"
123 with hinge 1234 without hinge <small>Overlay Hinge Kit: P/N 4180-0314-XE Thick Doors Kit: P/N 4180-0313-XE</small>		●		●			30 lbs.	42"	13/16" * MIN.
1155 Easy-Down			●				30 lbs.	48"	3/4"
1332 with hinge 1432 without hinge <small>Overlay Hinge Kit: P/N 4180-0314-XE Thick Doors Kit: P/N 4180-0313-XE 35mm Extra Hinge Kit: P/N 4180-0407-XE Black Hinge Carrier Strip Kit: P/N 4180-0408-XE</small>				●			75 lbs.	78"	13/16"*
1321						●	30 lbs.	42"	3/4" FULL OVERLAY 1-1/2" INSET

* Becomes 1-1/4" when using 40 mm cup hinge.

** For pocket doors. This is width on flipper doors.

♦ Varies depending on hinge used.

ACCU-RULE: Add one hinge for each foot over 36"

Accuride[®]
www.accuride.com



CABINET HARDWARE

SLIDE REFERENCE GUIDE

Accuride[®]

LIGHT DUTY 35 TO 75 LBS.	3/4 EXTENSION	LOAD RATING	ACCURIDE SPEEDSHIP	DISTRIBUTOR STOCKED	SIDE SPACE	MOUNTING	HOLE PATTERN	DETENTS	DISCONNECTS	MAXIMUM DRAWER WIDTHS	BALL BEARINGS	FINISHES
	1029	35 lbs.		○		Under	Traditional	None	Friction	16"	Steel	Zinc, Black*
	2037	50 lbs.		○	.52" [13.2 mm]	Side	Traditional	None	Rail	12"	Polymer	Zinc, Black*
	2632 Full Extension	65 lbs.	•	○	.50" [12.7 mm]	Side	Trad/32 mm	Hold In	Rail	16"	Steel	Zinc, Black*
	2132	75 lbs.	•	○	.50" [12.7 mm]	Side	Trad/32 mm	Hold In	Lever	16"	Steel	Zinc, Black*
MEDIUM DUTY 75 TO 100 LBS.	FULL EXTENSION	LOAD RATING	ACCURIDE SPEEDSHIP	DISTRIBUTOR STOCKED	SIDE SPACE	MOUNTING	HOLE PATTERN	DETENTS	DISCONNECTS	MAXIMUM DRAWER WIDTHS	BALL BEARINGS	FINISHES
	3834 Over Travel	90 lbs.	•	○	.50" [12.7 mm]	Side	Traditional	Hold In	Lever	16"	Steel	Zinc, Black*
	3132EC/SC	100 lbs.		○		Under	Trad/32 mm	None	Lever	30"	Steel/Polymer	Zinc
	3732	100 lbs.		○	.50" [12.7 mm]	Side	Trad/32 mm	Hold In	Latch	16"	Steel - C, CB/Polymer - EW	Zinc, Black*, Whire*
	3832	100 lbs.	•	○	.50" [12.7 mm]	Slide	Trad/32 mm	Hold In	Lever	16"	Steel - C, CB/Polymer - EW	Zinc, Black*, Weather Resistant*
	7432	100 lbs.	•	○	.50" [12.7 mm]	Rail	Trad/32 mm	Hold In	Rail	24"	Steel	Zinc, Black*
	7434 Over Travel	100 lbs.	•	○	.50" [12.7 mm]	Rail	Trad/32 mm	Hold In	Rail	24"	Steel	Zinc, Black*
3017 Over Travel	100 lbs.	•	○	.50" [12.7 mm]	Rail	Traditional	Hold In	Rail	24"	Polymer	Zinc, Black*	
HEAVY DUTY 100 TO 500 LBS.	FULL EXTENSION	LOAD RATING	ACCURIDE SPEEDSHIP	DISTRIBUTOR STOCKED	SIDE SPACE	MOUNTING	HOLE PATTERN	DETENTS	DISCONNECTS	MAXIMUM DRAWER WIDTHS	BALL BEARINGS	FINISHES
	4033	100 lbs.		○	.50" [12.7 mm]	Rail	Trad/32 mm	Hold In	Rail	18"	Polymer	Zinc, Black*
	4035 Over Travel	100 lbs.		○	.50" [12.7 mm]	Rail	Trad/32 mm	Hold In	Rail	18"	Polymer	Zinc, Black*
	4032	150 lbs.		○	.50" [12.7 mm]	Rail	Trad/32 mm	Hold In	Rail	27"	Steel	Zinc, Black*
	4034 Over Travel	150 lbs.	•	○	.50" [12.7 mm]	Rail	Trad/32 mm	Hold In	Rail	24"	Steel	Zinc, Black*
	3641 Over Travel	180 lbs.	•	○	.89" [22.6 mm]	Side	Trad/32 mm	Hold In	Rail	42"	Steel	Zinc, Black*
	3640 Over Travel – Under	75 lbs.	•	○	.89" [22.6 mm]	Under	Traditional	Hold In	Rail	24"	Steel	Zinc, Black*
	3640 Over Travel – Side	200 lbs.	•	○	.89" [22.6 mm]	Side	Traditional	Hold In	Rail	42"	Steel	Zinc, Black*
	9301 Flat Mount	150 lbs.	•	○	.89" [22.6 mm]	Under	Traditional	Hold In	None	32"	Steel	Zinc, Black*
	Mobile/Vehicular Use	300 lbs.		○	.75" [19.1 mm]	Side	Traditional	None	None	32"	Steel	Zinc
	Frequent Use	400 lbs.		○	.75" [19.1 mm]	Side	Traditional	None	None	42"	Steel	Zinc
	Moderate Use	500 lbs.		○	.75" [19.1 mm]	Side	Traditional	None	None	18"	Steel	Zinc
	Bracket-Mounted	350 lbs.		○	See Data Sheet		Traditional	None	None	42"	Steel	Zinc
Bracket-Mounted	500 lbs.		○	See Data Sheet		Traditional	None	None	18"	Steel	Zinc	
SPECIALTY 45 TO 325 LBS.	SPECIALTY	LOAD RATING	ACCURIDE SPEEDSHIP	DISTRIBUTOR STOCKED	SIDE SPACE	MOUNTING	HOLE PATTERN	DETENTS	DISCONNECTS	MAXIMUM DRAWER WIDTHS	BALL BEARINGS	FINISHES
	2006	45 lbs.	•	○	.44" [11.2 mm]	Side/Bracket	Traditional	None	Friction	16"	Steel	Zinc, Black*
	2002	50 lbs.	•	○	.38" [9.7 mm]	Side/Tab	Traditional	Center	None	12"	Steel	Zinc, Black*
	CBERGO-TRAY200			○		Bracket	Traditional	In and Out	None	29.6"	Steel	Black
	2109	75 lbs.	•	○	.66" [16.8 mm]	Side/Bracket	Traditional	In and Out	Lever	16"	Steel	Zinc, Black*
	CBERGO-TRAY300		•	○		Bracket	Traditional	In, Out & Intermediate	None	29.6"	Steel	Black
	322	100 lbs.	•	○	.76" [19.3 mm]	Side/Tab	Traditional	None	None	16"	Steel	Zinc, Black*
	340	110 lbs.	•	○	.87" [22.1 mm]	Side/Bracket	Traditional	None	Bracket	18"	Steel	Zinc, Black*
	301-2590	130 lbs.	•	○	.76" [19.3 mm]	Bracket/Under	Traditional	Hold In	None	16"	Steel	Zinc, Black*
	3600-200	175 lbs.	•	○	.83" [21.0 mm]	Side	Traditional	Hold In	None	16"	Steel	Zinc
	3600-201	175 lbs.	•	○	.90" [22.9 mm]	Top/Bottom/Bracket	Traditional	Hold In	Lever	16"	Steel	Zinc
	CB3620-258TV	225 lbs.	•	○		Shelf	Traditional	Hold In	Lever	36" Diagonal TV	Steel	Black
	CB9320-258TV	325 lbs.	•	○		Shelf	Traditional	Hold In - Slide Center - Swivel Plate	None	up to 65" wide	Steel	Black
	CBMAC-50	150 lbs.	•	○		Bracket	Traditional	In and Out	None	20-3/4" W x 18" D X 36" tall	Steel	Slides:black/Swivel plate: black powder coat
CBMAC-100	300 lbs.	•	○		Bracket	Traditional	In and Out	None	20-3/4" W x 18" D & 55" tall	Steel	Slides:black/Swivel plate: black powder coat	
FLIPPER DOORS 25 TO 75 LBS.	FLIPPER DOOR SLIDES	MAX. DOOR WEIGHT/SIZE	ACCURIDE SPEEDSHIP	DISTRIBUTOR STOCKED	MOUNTING	DETENTS	BALL BEARINGS	FINISHES				
	117	25 lbs./36"		○	Horizontal/Vertical	Hold Out (optional)	Steel	Zinc, Black*				
	1145	30 lbs./36"		○	Horizontal	None	Steel	Zinc, Black*				
	123	30 lbs./42"	•	○	Horizontal/Vertical	Hold Out	Steel	Black				
	1234	30 lbs./42"		○	Horizontal/Vertical	Hold Out	Steel	Black				
	1155	30 lbs./48"	•	○	Horizontal	None	Steel	Zinc, Black*				
	1321	30 lbs./42"	•	○	Vertical	None	Steel	Black				
	1332	75 lbs./78"	•	○	Vertical	Hold Out	Steel	Zinc*, Black				
1432	75 lbs./78"	•	○	Vertical	Hold Out	Steel	Zinc*, Black					